

MSDS for Crash Cart Box



NOVA Chemicals®

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

Section 1 - Product and Company Identification

Synonyms: Impact modified polystyrene, HIPS
Chemical Name: Polystyrene
Chemical Family: Polymer
Material Use: Petrochemical industry: Plastics
Chemical Formula: (C₈H₈ C₄H₆)_x

**#10
Approved**
8-6-02

NOVA Chemicals Inc.
1550 Coraopolis Heights Road
Moon Township, PA 15108

In case of Emergency

1-800-561-6682, 1-403-314-8767 (NOVA Chemicals)(24 hours)
1-800-424-9300 (CHEMTREC-USA)
1-613-996-6666 (Canutec-Canada)(24 hours)

Section 2 - Composition / Information on Ingredients

CAS #	Component	Percent by Wt.
9003-55-8	Styrene-Butadiene polymer	94-100

Component Related Regulatory Information

This product may be regulated, have exposure limits or other information identified as the following: Nuisance particulates.

Additional Information

This product is not considered hazardous under 29 CFR 1910.1200 (Hazard Communication). This material is not a controlled product under Canadian WHMIS regulations.

See Section 8 for applicable exposure limits. See Section 11 for applicable toxicity data.

Section 3 - Hazards Identification

HMIS Ratings: Health: 0* Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings: Health: 0 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Emergency Overview

Product is a white, inert, solid bead or pellet with slight odor. Nonflammable, but will burn on prolonged exposure to flame or high temperature. Slipping hazard.

Potential Health Effects: Eyes

Contact with hot or molten material may cause severe thermal burns. Contact with eye may cause mechanical irritation.

Potential Health Effects: Skin

Contact with hot or molten material may cause severe thermal burns. Mechanical rubbing may increase skin irritation.

Potential Health Effects: Ingestion

Ingestion of this product is unlikely. However, ingestion of product may produce gastrointestinal irritation and disturbances.

Potential Health Effects: Inhalation

Fumes released during thermal processing may cause irritation to the respiratory system.

Section 4 - First Aid Measures

First Aid: Eyes

Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention.

MSDS for Crash Cart Box

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

First Aid: Skin

Wash the affected skin gently and thoroughly with running water and non-abrasive soap. Seek medical attention if symptoms develop or persist.

First Aid: Hazardous Skin Contact

In case of contact with molten product, cool rapidly with water and seek immediate medical attention. DO NOT attempt to remove molten product, or molten product that has cooled, from skin because skin without medical assistance.

First Aid: Inhalation

Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

First Aid: Hazardous Inhalation

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform rescue breathing. WARNING: It may be dangerous to the person providing aid to perform rescue breathing when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

First Aid: Ingestion

DO NOT induce vomiting. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform rescue breathing. Seek immediate medical attention.

First Aid: Notes to Physician

Treat symptomatically. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

Section 5 - Fire Fighting Measures

Flammability Class:	Nonflammable	Flash Point:	345° to 360°C (653° to 680°F) (Combustible Flash Ignition Temperature)
Upper flammability limit:	Not available	Lower flammability limit:	Not available
Auto Ignition:	427°C (800°F)		

General Fire Hazards

Nonflammable, but will burn on prolonged exposure to flame or high temperature.

Hazardous Combustion Products

Styrene, butadiene, carbon dioxide, carbon monoxide.

Extinguishing Media

Dry chemical, foam, carbon dioxide, water fog or water spray. Do not use direct water stream.

Fire Fighting Equipment/Instructions

Full-face, NIOSH-approved self-contained breathing apparatus and appropriate protective clothing must be worn by all individuals required to enter the hazard area.

Section 6 - Accidental Release Measures

Evacuation Procedures

Keep unnecessary personnel out of the area.

Small Spills

Spilled product may create a dangerous slipping hazard. Use appropriate tools to put the spilled solid in an appropriate waste disposal container. Prevent entry into sewers, drains, underground or confined spaces, water intakes, and waterways.

Large Spills

Sweep up or gather material and place in appropriate container for disposal. Prevent entry into sewers, drains, underground or confined spaces, water intakes, and waterways.

Special Procedures

Contact local police and appropriate emergency telephone numbers provided in Section 1. Ensure statutory and regulatory reporting requirements in the applicable jurisdiction are met. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed.

MSDS for Crash Cart Box

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

Section 7 - Handling and Storage

Handling Procedures

Use with adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation. Handle in contained and properly designed equipment systems. Keep away from uncontrolled heat. Ground all material handling and transfer equipment to dissipate build-up of static electricity. Keep handling areas free of loose pellets and dust generation and accumulation. Spilled product may create a dangerous slipping hazard. Keep from contact with strong oxidizing materials.

Incompatibility

Not resistant to oxidizing agents, dissolves in organic solvents.

Storage Procedures

Storage area should be clearly identified, well-illuminated, clear of obstruction and accessible only to trained and authorized personnel. Store in grounded, properly designed and approved vessels and away from incompatible materials. Store and use away from heat, sparks, open flame, or any other ignition source. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically-safe electrical systems. Small amounts of fines or dust contained in granular resins may accumulate in material handling systems. If permitted to accumulate, these fines or dust can, under certain conditions, pose an explosion hazard. Every effort should be made to prevent the suspension, concentration or accumulation of fines or dusts in, or around, material handling systems. Further information can be obtained from NFPA-654. "Standard for the Prevention of Fire and Dust Explosions in Chemical, Dye, Pharmaceutical and Plastics Industries." DO NOT enter filled bulk containers and attempt to walk over product, due to risk of slipping and suffocation. Use a fall arrest system when working near open bulk storage containers.

Section 8 - Exposure Controls / Personal Protection

Exposure Guidelines

A: General Material Information

Follow all applicable exposure limits.

B: Component Exposure Limits

ACGIH and OSHA exposure limit lists have been checked for those components with CAS registry numbers.

Styrene-Butadiene polymer (9003-55-8)

- ACGIH: 10 mg/m³ TWA (inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica); 3 mg/m³ TWA (respirable fraction, particulate matter containing no asbestos and <1% crystalline silica) (related to Particulates not otherwise specified (PNOS))
- OSHA: 15 mg/m³ TWA (total dust); 5 mg/m³ TWA (respirable fraction) (related to Particulates not otherwise regulated)

Engineering Controls

If user operations generate dusts, mists, or fumes, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Personal Protective Equipment: Eyes/Face

Wear safety glasses during normal handling. Wear full face shield during thermal processing.

Personal Protective Equipment: Skin/Hands/Feet

Normal work clothing (long sleeved shirts and long pants) is recommended. Impervious gloves should be worn when handling product.

Personal Protective Equipment: Respiratory

When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH approved respiratory protection must be provided.

Personal Protective Equipment: General

Personal protective equipment (PPE) must not be considered a long term solution to exposure control. PPE must be accompanied by employer programs to properly select, maintain, clean, fit and use equipment. Consult a competent industrial hygiene resource to determine hazard potential and/or the PPE manufacturers and applicable regulations to ensure adequate protection.

MSDS for Crash Cart Box

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

Section 9 - Physical & Chemical Properties

Physical state and appearance:	White solid beads or pellets	Color:	White
Odor:	Slight odor	pH:	Not applicable
Vapor Pressure:	Not applicable	Vapor Density (Air=1):	Not applicable
Boiling Point:	Not applicable	Melting Point:	105°C to 135°C (221°F to 275°F)
Solubility (H2O):	Insoluble	Specific Gravity (Water=1):	1.04 g/cc, 104 kg/m
Softening Point:	79°C to 127°C (174°F to 261°F)	Evaporation Rate (n-Butyl Acetate=1):	Not applicable

Section 10 - Stability & Reactivity Information

Chemical Stability

This is a stable material.

Instability

Decomposition temperature: 300°C (572°F)

Chemical Stability: Conditions to Avoid

Avoid processing material over 300°C (572°F).

Incompatibility

Not resistant to oxidizing agents, dissolves in organic solvents.

Hazardous Polymerization

Will not occur.

Corrosivity

Not expected to be corrosive.

Hazardous Decomposition

Styrene, butadiene, carbon dioxide, carbon monoxide

Section 11 - Toxicological Information

Acute Toxicity

A: General Material Information

Polystyrene homopolymer may be irritating to the eyes. Skin contact with molten or heated material can cause burns.

B: Acute Toxicity - LD50/LC50

No LD50/LC50's are available for this product's components.

Chronic Toxicity

A: General Material Information

No additional information available.

B: Carcinogenic Effects

ACGIH, IARC, OSHA, and NTP carcinogen lists have been checked for those components with CAS registry numbers.

Styrene-Butadiene polymer (9003-55-8)

IARC: Supplement 7, 1987; Monograph 19, 1979 (Group 3 (not classifiable))

Section 12 - Ecological Information

Ecotoxicity

A: General Material Information

The information below is based on a knowledge of the components and the ecotoxicity of similar products. Sewer/waterway obstruction; marine life may ingest pellets, which may obstruct their digestive tract. Product is expected to be non-toxic, but small particles may have physical effects on aquatic and terrestrial organisms.

Environmental Fate

See information below.

MSDS for Crash Cart Box

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

Mobility

Sinks in water.

Persistence/Degradability

Pellets may accumulate in the digestive systems of birds and aquatic life, causing injury and possible death. Do not allow product to enter sewer or waterways. Expected to be inherently non-biodegradable.

Bioaccumulation/Accumulation

Not expected to bioaccumulate significantly.

Section 13 - Disposal Considerations

North America Waste Number & Descriptions

A: General Material Information

This product, if discarded, is not expected to be considered a hazardous waste according to US RCRA and Canadian regulations. Check Local, State, Federal, and Provincial Environmental Regulations prior to disposal. Preferred disposal methods are: 1) clean and reuse if possible; 2) contact resin broker; 3) contact plastic recycler; 4) incinerate with waste heat recovery and/or 5) landfill. Reuse, recycling, storing, transportation, and disposal must be in accordance with applicable federal, state/provincial and local regulation. DO NOT ATTEMPT TO DISPOSE OF BY UNCONTROLLED IGNITION.

B: Component Waste Numbers

No EPA Waste Numbers are applicable for this product's components.

Section 14 - Transportation Information

US DOT Information

Shipping Name: This material is not regulated as a hazardous material for transportation.

Canadian TDG Information

Shipping Name: This material is not regulated as a hazardous material for transportation.

International Air Transport Association (IATA) Regulations

Shipping Name: This material is not regulated as a hazardous material for transportation.

International Maritime Dangerous Goods (IMDG) Code

Shipping Name: This material is not regulated as a hazardous material for transportation.

Section 15 - Regulatory Information

U.S. Federal Regulations

A: General Material Information

No information available.

B: Component Analysis

None of this product's components are listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), or CERCLA (40 CFR 302.4).

C: Component Analysis - U.S. State

Some components (including those present only in trace quantities, and therefore not listed in this document) may be included on the Right To Know lists of other U.S. states. The reader is therefore cautioned to contact his or her NOVA Chemicals representative or NOVA Chemicals' Product Integrity group for further U.S. State Right-To-Know information.

None of this products components are listed on the state lists from NJ or PA.

D: Component Analysis - WHMIS IDL

No components are listed in the WHMIS IDL.

U.S. State Regulations

Other U.S. state regulations may apply. Check individual U.S. state requirements.

MSDS for Crash Cart Box

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

Canadian Provincial Regulations

No information available.

Other Regulations

A: General Material Information

The monomer is listed by EINECS for polystyrene homopolymer.

B: Component Analysis - Inventory Status

Component	CAS #	US - TSCA	CANADA - DSL	EU - EINECS
Styrene-Butadiene polymer	9003-55-8	Yes	Yes	No

Canadian Environmental Protection Act (CEPA): This product is on the Domestic Substances List (DSL), and is acceptable for use under the provisions of CEPA.

WHMIS Classification

Workplace Hazardous Materials Information Systems (WHMIS): This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations, and the MSDS contains all of the information required by the Controlled Products Regulations. Not controlled under WHMIS (Canada).

Section 16 - Other Information

Label Information

PRECAUTIONS: Product is a white, inert, solid bead or pellet with slight odor. Nonflammable, but will burn on prolonged exposure to flame or high temperature. Slipping hazard.

FIRST AID:

SKIN: For contact with molten product, do not remove any material or clothing adhering to the skin. Flush the burned area immediately with large amounts of cold water. If it is possible, submerge the area in cold water. Immediately seek medical attention or contact a physician.

EYES: Immediately flush eyes with water for at least 15 minutes, while holding eyelids open. Seek medical attention.

INHALATION: Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform rescue breathing. **WARNING:** It may be dangerous to the person providing aid to perform rescue breathing when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

INGESTION: DO NOT induce vomiting. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform rescue breathing. Seek immediate medical attention.

IN CASE OF A LARGE SPILL: Spilled product may create a dangerous slipping hazard. Use appropriate tools to put the spilled solid in an appropriate waste disposal container.

References

Not available

Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists; BOD = Biochemical Oxygen Demand; CAS = Chemical Abstracts Service; CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act; CPR = Controlled Products Regulations; DOT = Department of Transportation; DSL = Domestic Substances List; EINECS = European Inventory of Existing Commercial Substances; EPA = Environmental Protection Agency; EU = European Union; FDA = Food and Drug Administration; IARC = International Agency for Research on Cancer; IDL = Ingredient Disclosure List; Kow = Octanol/water partition coefficient; NIOSH = National Institute for Occupational Safety and Health; NJTSR = New Jersey Trade Secret Registry; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration; RCRA = Resource Conservation and Recovery Act; SARA = Superfund Amendments and Reauthorization Act; TDG = Transportation of Dangerous Goods; TSCA = Toxic Substances Control Act.

Validated by Product Integrity Group on 06/26/02 Verified by Product Steward.

Contact: Product Integrity Group
NOVA Chemicals Corporation

MSDS for Crash Cart Box

Material Safety Data Sheet

Material Name: Impact Polystyrene, Natural Grades

MSDS ID: NOVA-0056

6711 Mississauga Road, Suite 200
Mississauga, Ontario L5N 2W3
Contact Phone: 905-542-6980

Other Information

Notice to Reader

ALTHOUGH THE INFORMATION CONTAINED IN THIS DOCUMENT IS PRESENTED IN GOOD FAITH, BASED ON AVAILABLE INFORMATION BELIEVED TO BE RELIABLE AT THE TIME OF PREPARATION OF THIS DOCUMENT, NOVA CHEMICALS MAKES NO WARRANTIES OR REPRESENTATIONS WITH RESPECT TO THE INFORMATION OR THE PRODUCTS DESCRIBED HEREIN, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES AND CONDITIONS (INCLUDING ALL WARRANTIES AND CONDITIONS OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT NOTICE.

RESPONSIBILITY FOR USE, STORAGE, HANDLING AND DISPOSAL OF THE PRODUCTS DESCRIBED HEREIN, WHETHER ALONE OR IN COMBINATION WITH ANY OTHER SUBSTANCE, IS THAT OF THE PURCHASER AND/OR END USER.

 **NOVA Chemicals®** is a Registered Trademark of NOVA Brands Ltd.; authorized use

This is the end of MSDS # NOVA-0056

MSDS for Slide-in Lid



PLEXIGLAS (R) MC Acrylic Sheet

Material Safety Data Sheet

ATOFINA Chemicals, Inc.

1 PRODUCT AND COMPANY IDENTIFICATION

Atoglas Sheet
ATOFINA Chemicals, Inc.
2000 Market Street
Philadelphia, PA 19103

EMERGENCY PHONE NUMBERS:
Chemtrec: (800) 424-9300 (24hrs) or (703) 527-3887
Medical: Rocky Mountain Poison Control Center
(303) 823-5716 (24Hrs)

Information Telephone Numbers

Phone Number

Available Hrs

Atoglas Customer Service

(800) 523-1532

8:00 am - 6:00pm EST

Product Name PLEXIGLAS (R) MC Acrylic Sheet
Product Synonym(s)

Chemical Family Acrylic Copolymer

Chemical Formula N/A

Chemical Name See Ingredients

EPA Reg Num

Product Use

2 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS Registry Number	Typical Wt. %	OSHA
2-Propenoic acid, 2-methyl-methyl ester, polymer with ethyl 2-propenoate	9010-88-2	99.2 MINIMUM	N
Methyl methacrylate	80-82-8	0.5 MAXIMUM	Y
Ethyl acrylate	140-88-5	<0.1	Y

The substance(s) marked with a "Y" in the OSHA column, are identified as hazardous chemicals according to the criteria of the OSHA Communication Standard (29 CFR 1910.1200)

While this material is not classified as hazardous under Federal OSHA regulations, this MSDS contains valuable information critical to the safe handling and proper use of this product. This MSDS should be retained and available for employees and other users of this product.

The components of this product are all on the TSCA inventory list.

3 HAZARDS IDENTIFICATION

Emergency Overview

Clear to opaque sheet in various colors. Odorless.

CAUTION!

MAY CAUSE EYE AND SKIN IRRITATION.

MAY CAUSE RESPIRATORY TRACT IRRITATION.

Potential Health Effects

Skin contact and inhalation of dust are expected to be the primary routes of occupational exposure to this material. As a finished product, it is a synthetic, high molecular weight polymer pellet. Due to its chemical and physical properties, this material does not require special handling other than the good industrial hygiene and safety practices employed with any industrial material of this type.

Call Free: 1 800 848 1633 or 1 888 HCL INTL® (425 4685) • Fax Free: 1 800 447 2923

Web Site: www.HealthCareLogistics.com • E-mail: hcl@HealthCareLogistics.com

MSDS for Slide-in Lid



PLEXIGLAS (R) MC Acrylic Sheet

Material Safety Data Sheet
ATOFINA Chemicals, Inc.

4 FIRST AID MEASURES

IF IN EYES, immediately flush with plenty of water. Get medical attention if irritation persists.

IN CASE OF CONTACT, flush the area with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention if irritation develops and persists.

IF INHALED, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

5 FIRE FIGHTING MEASURES

Fire and Explosive Properties

Auto-Ignition Temperature	>400 C/752 F	
Flash Point	NA	Flash Point Method
Flammable Limits- Upper	NA	
Lower	NA	

Extinguishing Media

Use water spray, carbon dioxide, foam or dry chemical.

Fire Fighting Instructions

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

Fire and Explosion Hazards

Heated material can form flammable vapors with air.

6 ACCIDENTAL RELEASE MEASURES

In Case of Spill or Leak

Contain spill. Sweep or scoop up and remove to suitable container. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

7 HANDLING AND STORAGE

Handling

Avoid temperature extremes during storage; ambient temperature preferred.

Storage

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container closed. Use only with adequate ventilation.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

MSDS for Slide-in Lid



PLEXIGLAS (R) MC Acrylic Sheet
 Material Safety Data Sheet
 ATOFINA Chemicals, Inc.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls

Investigate engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to control exposure levels below airborne exposure limits (see below). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Eye / Face Protection

Use good industrial practice to avoid eye contact.

Skin Protection

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Rinse contaminated skin promptly. Wash contaminated clothing and clean protective equipment before reuse. Wash skin thoroughly after handling.

Respiratory Protection

Avoid breathing dust. When airborne exposure limits are exceeded (see below), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Consult respirator manufacturer to determine appropriate type equipment for given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Airborne Exposure Guidelines for Ingredients

Exposure Limit	Value
Ethyl acrylate	
ACGIH STEL	15 ppm; 61 mg/m ³
ACGIH TWA	5 ppm 20 mg/m ³
OSHA Skin designator	Y
OSHA TWA PEL	25 ppm 100 mg/m ³
Methyl methacrylate	
ACGIH Sensitizer designator	Y
ACGIH STEL	100 ppm (410 mg/m ³)
ACGIH TWA	50 ppm (205 mg/m ³)
OSHA TWA PEL	100 ppm (410 mg/m ³)

-Only those components with exposure limits are printed in this section.

-Skin contact limits designated with a "Y" above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required.

-ACGIH Sensitizer designator with a value of "Y" above means that exposure to this material may cause allergic reactions.

MSDS for Slide-in Lid



PLEXIGLAS (R) MC Acrylic Sheet

Material Safety Data Sheet

ATOFINA Chemicals, Inc.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor	Clear to opaque sheet in various colors. Odorless.
pH	na
Specific Gravity	1.15 to 1.19
Vapor Pressure	NA
Vapor Density	NA
Melting Point	132 C/270 F
Freezing Point	NA
Boiling Point	NA
Solubility In Water	insoluble
Percent Volatile	0

10 STABILITY AND REACTIVITY

Stability

This material is chemically stable under normal and anticipated storage and handling conditions.

Hazardous Polymerization

Does not occur.

Incompatibility

Prolonged contact with acids, alkalis and strong oxidizing agents may attack or dissolve the polymer.

Hazardous Decomposition Products

Thermal decomposition may yield acrylic monomers.

11 TOXICOLOGICAL INFORMATION

Toxicological Information

No data are available.

12 ECOLOGICAL INFORMATION

Ecotoxicological Information

No data are available.

Chemical Fate Information

No data are available.

13 DISPOSAL CONSIDERATIONS

Waste Disposal

Incineration is the recommended method for disposal observing all local, state and federal regulations.

Call Free: 1 800 848 1633 or 1 888 HCL INTL® (425 4685) • Fax Free: 1 800 447 2923

Web Site: www.HealthCareLogistics.com • E-mail: hcl@HealthCareLogistics.com

MSDS for Slide-in Lid



PLEXIGLAS (R) MC Acrylic Sheet
 Material Safety Data Sheet
 ATOFINA Chemicals, Inc.

14 TRANSPORT INFORMATION

DOT Name NOT REGULATED
 DOT Technical Name
 DOT Hazard Class
 UN Number
 DOT Packing Group PG
 RQ

15 REGULATORY INFORMATION

Hazard Categories Under Criteria of SARA Title III Rules (40 CFR Part 370)

Immediate (Acute) Health	Y	Fire	N
Delayed (Chronic) Health	N	Reactive	N
		Sudden Release of Pressure	N

The components of this product are all on the TSCA inventory list.

Ingredient Related Regulatory Information:

SARA Reportable Quantities	CERCLA RQ	SARA TPQ
Ethyl acrylate	1000 LBS	NE
Methyl methacrylate	1000 LBS	
2-Propenoic acid, 2-methyl-methyl ester, polymer with ethyl 2-propenoate	NE	

SARA Title III, Section 313

This product does contain chemical(s) which are defined as toxic chemicals under and subject to the reporting requirements of, Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1980 and 40 CFR Part 372. See Section 2

Ethyl acrylate
 Methyl methacrylate

California Prop 65 - Carcinogen

This product does contain the following chemical(s), as indicated below, currently on the California list of Known Carcinogens

Ethyl acrylate

Massachusetts Right to Know

This product does contain the following chemical(s), as indicated below, currently on the Massachusetts Right to Know Substance List.

Ethyl acrylate
 Methyl methacrylate

New Jersey Right to Know

This product does contain the following chemical(s), as indicated below, currently on the New Jersey Right-to-Know Substances List.

Ethyl acrylate
 Methyl methacrylate

Pennsylvania Environmental Hazard

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Environmental Hazard List.

Ethyl acrylate
 Methyl methacrylate

Pennsylvania Right to Know

MSDS for Slide-in Lid



PLEXIGLAS (R) MC Acrylic Sheet

Material Safety Data Sheet
ATOFINA Chemicals, Inc.

Pennsylvania Right to Know

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Hazardous Substance List.

Ethyl acrylate
Methyl methacrylate

Pennsylvania Special Hazard

This product does contain the following chemical(s), as indicated below, currently on the Pennsylvania Special Hazard List.

Ethyl acrylate

16 OTHER INFORMATION

Revision Information

Revision Date 29 JUN 2000 Revision Number 10
Supersedes Revision Dated 16-JUN-2000

Revision Summary

Key

NE= Not Established NA= Not Applicable (R) = Registered Trademark

ATOFINA Chemicals, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of ATOFINA Chemicals, ATOFINA Chemicals expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.